

LED Driver C.V Model**24V,C.V. SERIES****Design Highlight:**

- Build-in Type.
- Constant Voltage design for high-Power LED
- Universal Full Range input.
- PF >0.75
- High Efficiency >80%
- 100% Hi-pot test
- High Reliability
- Single output channel
- RoHS compliant
- OEM Version

**General Spec**

Input Voltage : 90Vac- 264Vac
 Input Frequency: 47Hz-63Hz

Operating Temperature: -20°C to +60°C
 Storage Temperature: -20°C to +85°C
 Operating humidity: 20% to 85% RH
 Storage humidity: 10% to 95% RH

Compliance below international Standards.

EMI Standards: EN55015 EN61347-1
 EMS Standards: IEC 61000
 Safety Compliance: EN61347-2-13 CE
 UL1310

MTBF: 100.000 hours at ambient 25°C
 Life Test:
 Leakage Current: 240V/50Hz/0.25mA max
 Complete Protection: Short Circuit,Over Voltage,Over Power
 Over Temperatur ,Fuse Protection

24V C.V. Series

Model	O/P Wattage	Output Rating			Efficiency*	PF**	Dimension (mm)		
		Vc.v	Imin	Imax			L	W	H
FSP032-1ZA2	32W	24V	0	1.35A	80%	0.75	150	40	21

Note

*Typical load ** 220V full load condition

Mechanical Specification

